



Flooring
assortment 2024

www.krono-original.com


Krono
Original
High Quality
Made by Kronospan

Welcome to our world!

FEATURES GUIDE	04
PRODUCT OVERVIEW	06

Organic VENEER PARQUET	08
Rocko SPC Flooring	18
O.R.C.A. Flooring	50
Organic FLEX	56
Organic LONG	66
Organic CLASSIC	72
Organic CLEVER SILENT	86

mo.re! Laminate Flooring	94
HERRINGBONE 8	98
ALTITUDE	104
ATLANTIC 12	110
ATLANTIC 10	116
ATLANTIC 8	130
Classic Laminate Flooring	146
SUPER NATURAL	150
CASTELLO	172

FORMAT OVERVIEW	178
ACCESSORIES	180
SKIRTING BOARDS	186
DECOR OVERVIEW	188
PACKAGING INFORMATION	190



www.krono-original.com


www.facebook.com/KronoOriginal



Organic VENEER PARQUET




Rocko SPC Flooring




mo.re! Laminate Flooring



O.R.C.A. Flooring



Classic Laminate Flooring



Accessories

Features guide

Your benefits at a glance



Residential guarantee

All floors are put through a series of rigorous tests in order to comply with international quality standards, which is why we grant an extensive residential warranty with every product.



Real groove

Bevelled edges on all four sides of the plank ensure an authentic floorboard look.



Soft bevel

Inspired by traditional craftsmanship, the true-edge-bevels provide a harmonious room appearance.



Anti bacterial comfort

A.B.C. Anti Bacterial Comfort inhibits the growth of bacteria on your flooring and provides you with the peace of mind that comes from a healthy home environment. Tested germs: Staphylococcus aureus



Authentic embossed

The synchronous pores follow the grain of the decor, meaning they flawlessly mimic the character of natural wood.



Microscratch protect

The robust surface protects your flooring against micro-scratches that can be caused by strong mechanical stresses or the claws of house pets.



Pet-proof

Thanks to the robust surface, which is also undaunted by small mishaps, the flooring is exceptionally well-suited for life with house-pets.



Light-resistant

The flooring is light-resistant: Even on days when the sun is shining for hours, your flooring remains non-fading according to rating 6 of the Blue Wool Scale.



Silent

Due to an integrated pad, the flooring reduces impact sound, echoes and vibrations. An additional underlay is not required, which saves time and money.



Robust

This flooring is amazingly robust due to its super durable surface. Moving furniture or falling objects are not a problem because of its high pressure and impact resistance.



Warm underfoot

Due to its flexible design layer, the flooring has comfortable haptics and is warm underfoot.




Anti-slip class

Safety is something we put great emphasis on. Classification in anti-slip classes has been achieved through specially developed surface structures, which address the requirements for floor coverings in the workplace and commercial areas where a high risk of slipping is present.



Anti-slip class

Classification:
R9 and R10 according to DIN 51130 and DIN EN 16165, A and B according to DIN 51097 and DIN EN 16165



Design diversity

Up to 60 different panels on digitally printed design are possible. This lends your flooring an authentic appearance that is virtually free of repetition.



Soft touch

The flooring has a soft surface and feels very comfortable.



Real wood

This floor is made from real wood. The high-quality brushed oak surface gives every room natural elegance.









































Anti-static

The flooring provides complete protection against unpleasant shocks. The Anti-static is built-in and guaranteed for the life of the floor.



R150 Brenton





























Product overview

	Collection Name	Durability (Wear Resistance)	Coreboard (Water Protection)	Thickness
Veneer Parquet	Organic^{*1} VENEER PARQUET 1383 x 244 mm 54.45" x 9.61"	 Titanium Ultra	 ^{*2} m.re! moisture resistance technology 	8.5 mm
SPC Flooring	ROCKO 1210 x 192 mm 47.64" x 7.56"	 Titanium Ultra	 SPC 	5+1 mm PerfectPad [®] IXPE
	1210 x 192 mm 47.64" x 7.56" 1210 x 234 mm 47.64" x 9.21" 1210 x 295 mm 47.64" x 11.61"	 Titanium Ultra	 SPC 	5 mm
	Organic^{*1} FLEX 638 x 322 mm 25.12" x 12.68" 1288 x 189 mm 50.71" x 7.44"	 Titanium Ultra	 ^{*3} O.R.C.A.[®] MOISTURE DEFENSE TECHNOLOGY 	7 mm PerfectPad [®] Cork
O.R.C.A. Flooring	Organic^{*1} LONG 2003 x 195 mm 78.86" x 7.68"	 AC5	 ^{*3} O.R.C.A.[®] MOISTURE DEFENSE TECHNOLOGY 	8 mm
	Organic^{*1} CLASSIC 638 x 330 mm 25.12" x 12.99" 1288 x 195 mm 50.71" x 7.68"	 AC5	 ^{*3} O.R.C.A.[®] MOISTURE DEFENSE TECHNOLOGY 	8 mm
	Organic^{*1} CLEVER SILENT 1288 x 195 mm 50.71" x 7.68"	 AC5	 ^{*3} O.R.C.A.[®] MOISTURE DEFENSE TECHNOLOGY 	6+1 mm PS Pad
	HERRINGBONE 8 630 x 126 mm 24.80" x 4.96"	 AC5	 m.re! moisture resistance technology 	8 mm
more! Laminate Flooring	ALTITUDE 2003 x 245 mm 78.86" x 9.65"	 AC5	 ^{*4} m.re! moisture resistance technology 	12 mm
	ATLANTIC 12 1288 x 195 mm 50.71" x 7.68"	 AC5	 ^{*4} m.re! moisture resistance technology 	12 mm
	ATLANTIC 10 1288 x 195 mm 50.71" x 7.68"	 AC5	 ^{*4} m.re! moisture resistance technology 	10 mm
	ATLANTIC 8 638 x 330 mm 25.12" x 12.99" 1288 x 195 mm 50.71" x 7.68"	 AC4	 ^{*4} m.re! moisture resistance technology 	8 mm
	SUPER NATURAL 1288 x 195 mm 50.71" x 7.68"	 AC4	HDF	8 mm
Classic Laminate Flooring	CASTELLO 1285 x 192 mm 50.59" x 7.56"	 AC4	HDF	8 mm

*1 Consists of natural wood and an organic chemical binder

*2 Tested according to NALFA Laminate Surface Swell Test and according to ISO 4760 (Topical moisture resistance – Assembled joint)

*3 24 h surface water protection as stipulated by NALFA (North American Laminate Floor Association) with additional 100 h+ surface water protection according to works standard specification KRONOSPAN WN-101, www.100hour-test.com, up to 100 h no leakage based on ISO 4760:2022-05

Pet-proof	Utilization Class	Residential Guarantee ^{*5}	Bevel	Joint	Authentic Embossed	SKUs
	32 	20 years	Soft Bevel	Tap Loc	-	6
	34 	30 years	V4	1 clic 2go pure	-	8
	34 	30 years	V4	1 clic 2go pure	-	24
	34 	30 years	V4	1 clic 2go pure+	-	11
	33 	30 years	V4	1 clic 2go pure+	Yes	6
	33 	30 years	V4	1 clic 2go pure+	Yes ^{*6}	15
	32 	20 years	V4	1 clic 2go pure+	Yes	8
	32 	20 years	V4	Fold Down	Yes	4
	33 	30 years	V4	1 clic 2go pure+	Yes	6
	33 	30 years	V4	1 clic 2go pure+	Yes	6
	33 	30 years	V4	1 clic 2go pure+	Yes	15
	32 	20 years	V4	1 clic 2go pure+	Yes ^{*6}	21
	32 	20 years	V4	1 clic 2go pure+	Yes ^{*6}	27
	32 	20 years	-	twin clic	-	6

*4 24 h surface water protection as stipulated by NALFA and 48 h splash-water protection according to works standard KRONOSPAN WN-103, www.floor-with-more.com


*5 According to warranty terms

*6 Selected decors

Σ 163

The sustainable alternative to parquet

These wooden floorings are luxurious, cosy and natural. The high-quality brushed oak surface lends homely flair to any room. With the Veneer Parquet series, KRONOSPAN offers authentic wood floors with a real wood veneer as the top layer.



The special thing about it: KRONOSPAN combines the natural properties of the raw material wood with the technical refinements of a multi-layer construction. The top layer consists of a 0.6 millimeter wood veneer – the wood comes exclusively from sustainable forestry. The middle layer consists of a high-density fibreboard (HDF). This makes the flooring particularly stable and durable. Thanks to these properties, Veneer Parquet is a resource-saving and sustainable alternative to conventional parquet flooring.



The innovative feature, mo.re! technology, is the intelligent moisture protection. This means the real wooden surface of the floor is also protected for just in case.




Real wood



Feel the nature



LU Ultramatt surface



Real wood flair with protection against moisture

0273 Oak Bradford



organic

VENEER
PARQUET



Residential
guarantee



Utilization
class



Soft bevel

Ultramatt surface

Real wood flair

Eco-friendly

Wood from sustainably managed forests

Moisture resistant*

thanks to mo.re! technology

Soft bevel

True-Edge-Bevel for a harmonious room appearance

Easy installation

Ideal for renovations thanks to low profile height

Modern wide planks: 1383 x 244 mm

Amazing designs

* Tested according to NALFA Laminate Surface Swell Test and according to ISO 4760 (Topical moisture resistance — Assembled joint)

The sustainable alternative to parquet



O274 Oak Sunderland

organic

VENEER PARQUET

m.re!
moisture resistance technology

*moisture
resistant*

Thickness:
8.5 mm

Format:
1383 x 244 mm | 54.45" x 9.61"

Lock:
Tap Loc



EN 14354



Oak Cream
O350




Organic VENEER PARQUET




1383 mm
(54.45")
244 mm
(9.61")

Oak Sunderland
O274






O273
Oak Bradford, LU




O462
Oak Schönbrunn, LU




O274
Oak Sunderland, LU



Organic VENEER PARQUET




Oak Roast
0352



O350
Oak Cream, LU



O272
Oak Bristol, LU



O352
Oak Roast, LU



ROCKO

Flooring by Kronospan

Waterproof SPC flooring with superior performance

Innovative SPC floors with unique design

Waterproof Rocko Flooring, made of over 70 % of mineral core, finished with high-quality UV coating, is an outstanding material for domestic and commercial use, both in new projects and renovations.

Appearance of natural wood & stone

Rocko Flooring designs are digitally printed, reflecting the smallest detail, the rich grain of wood and roughness of stones and concrete.

Ensured stability


Rocko Flooring range is set apart from other types of vinyl flooring by its unique resilient core, which provides an incredibly stable base for each flooring plank and ensures dimensional stability, even with high temperature fluctuations.

Coordinated solution

Available in 3 different formats, allows for any design finishing, going beyond the standard flooring frame. It comes with complementary accessories: waterproof flooring skirting boards, underlay and cleaning liquid for coordinated solution.



Check out the
complete collection!



R065 Rope

A solid step up

R123 Nutmeg



ROCKO

Flooring by Kronospan



Waterproof

Rocko Flooring is suitable for indoor use in humid conditions, such as bathroom, laundry room, kitchen or vestibule.

Dimensional stability

Rocko Flooring does not change its dimensions under the influence of temperature and humidity changes. It can be used in sunny and shaded areas as well as in dry and humid ones.

Utility class

Due to its parameters, Rocko Flooring reaches the highest utility class. It can be used in intensively used domestic areas as corridor or kitchen, as well as in commercial spaces with high traffic, such as offices.

Underfloor heating

Rocko Flooring is well suited for underfloor heating, thanks to its mineral content and its very good thermal conductivity parameters.


V-groove

Real v-groove on 4 sides of each plank.





R129 White Poppy



R082 Humidor

ROCKO

with PerfectPad® IXPE 1 mm




Thickness:
5+1 mm

Format:
1210 x 192 mm | 47.64" x 7.56"

Lock:
1 clic 2go pure



EN 16511



Scandipure
R073



ROCKO




with **PerfectPad®** IXPE 1 mm



1210 mm
(47.64")
192 mm
(7.56")

Crescendo
R081



R073
Scandipure, HS




R081
Crescendo, HS

ROCKO




with **PerfectPad®** IXPE 1 mm




Rope
R065



R078
Airflow, HS



R065
Rope, HS






R077
Barista, HS




ROCKO



with **PerfectPad®** IXPE 1 mm



Incando
R070



ROCKO



Thickness:
5 mm

Formats:


1210 x 192 mm | 47.64" x 7.56"

1210 x 234 mm | 47.64" x 9.21"

1210 x 295 mm | 47.64" x 11.61"

Lock:

1clic 2go pure



EN 16511



Sculpta
R066



ROCKO




1210 mm
(47.64")
192 mm
(7.56")

Salt Mine
R079






R079
Salt Mine, SO



R078
Airflow, HS




R073
Scandipure, HS

ROCKO




Barista
R077






R077
Barista, HS



R065
Rope, HS






R076
Bourbon Cask, SO

ROCKO




Wild Agar
R171






R173
Marshal Oak, FN





R171
Wild Agar, FN




R081
Crescendo, HS


ROCKO




Sienna
R170



R170
Sienna, FN



R082
Humidor, SO



R070
Incando, SO

ROCKO



1210 mm
(47.64")
234 mm
(9.21")

Clamshell
R148





R148
Clamshell, SO




R066
Sculpta, HS

ROCKO




Brenton
R150

R172
Vigra Oak, FN



R150
Brenton, SO



ROCKO



1210 mm
(47.64")
295 mm
(11.61")

White Poppy
R129





R109
Concrete, PT




R129
White Poppy, SO




R125
Mornel, SO

ROCKO




Ascot
R128


R174
Salem Oak, FN




R128
Ascot, SO




ROCKO




Clove
R124



R123
Nutmeg, SO



R124
Clove, SO




R149
Brown Marten, SO



MOISTURE DEFENSE TECHNOLOGY

How O.R.C.A. technology works



Each fiber is encapsulated with a special binder that prevents it from absorbing water.

Short fiber length and geometry reduces potential swelling.

Micro expansion on the edges seals the connection between planks.






Wood's self sealing property

Wood expands when exposed to moisture and in doing so seals itself, preventing liquid penetration.

Boat builders take advantage of wood's natural self sealing property.

Wine barrels are still sealed using this time tested method.





MOISTURE DEFENSE TECHNOLOGY

The floor that combines the best

O.R.C.A. = Organic*¹ Rigid Coreboard Abrasion-proof

O.R.C.A. is twice as good

It unites the best qualities of biologically based floors and conventional waterproof floor coverings. In O.R.C.A., organic*¹ materials are made resistant to liquids by means of a special technology.

O.R.C.A. makes the flooring usable anywhere

The innovative O.R.C.A. board makes it possible to install the flooring even in private bathrooms*² where, until now, only vinyl or tiles could be used. Furthermore, thanks to their outstanding thermal stability and non-fading properties, O.R.C.A. products also can be used in conservatories and rooms with floor-to-ceiling windows.

O.R.C.A. floors are extremely robust

The robust surface with an AC5 durability rating, protects the flooring against microscratches that can be caused by strong mechanical stresses such as moving furniture, falling objects or the claws of house pets. Thanks to its durable properties, which are also undaunted by small mishaps, O.R.C.A. floors are exceptionally well-suited for life with house pets.

O.R.C.A. is built better because it is more elaborately manufactured

The wood fibers are mechanically processed multiple times in a special production process to obtain especially small fibers. Further on in the manufacturing process a specially developed, organic-chemical binding agent surrounds even the finest fibers and isolates them from moisture.

The floor that's not afraid of water

100 h+ splash-water protection guaranteed*³

Little accidents occur almost daily. Wherever such things are bound to happen, it's worth relying on O.R.C.A. Kitchen, dining room, bathroom – O.R.C.A. is a perfect fit.



Scan the QR code and convince yourself!



*¹ Consists of natural wood and an organic chemical binder

*² Please observe installation instructions

*³ 24 h surface water protection as stipulated by NALFA (North American Laminate Floor Association) with additional 100 h+ surface water protection according to works standard specification KRONOSPAN WN-101, www.100hour-test.com, up to 100 h no leakage based on ISO 4760:2022-05



**So reliable
you can afford
to take the plunge**



O.R.C.A.[®]

MOISTURE DEFENSE TECHNOLOGY

The flooring that is naturally nature-friendly



www.blauer-engel.de/uz176



Sustainable

Sustainability isn't just a buzzword for us, but part of our corporate strategy. It would never cross our minds to use wood that didn't come from sustainably managed forests.

CO₂-negative

O.R.C.A. boards are CO₂-negative because manufacturing O.R.C.A. releases less CO₂ than was stored by the tree.

Organic

Our O.R.C.A. board consists of components based on biological raw materials and organic-chemical binding agents (synthetic resins) and thus is organic.

PVC-free

Our O.R.C.A. products contain no PVC*.



* May contain traces of PVC, e.g. from packaging





K500 Pearl River Oak



Organic FLEX

with **PerfectPad**® Cork 1 mm


O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



Thickness:
7 mm

Formats:
638 x 322 mm | 25.12" x 12.68"
1288 x 189 mm | 50.71" x 7.44"

Lock:
1clic 2go pure+



EN 16511



Pebble Manor Oak
K503





Organic FLEX  waterproof


with PerfectPad® Cork 1 mm



1288 mm
(50.71")
189 mm
(7.44")


Lunar Range Oak
K506






K500
Pearl River Oak, TN

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K503
Pebble Manor Oak, TN

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY




K506
Lunar Range Oak, TN

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY




Organic FLEX  waterproof

with **PerfectPad**® Cork 1 mm




Sand River Oak
K501




K501
Sand River Oak, TN

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K507
Hazel Range Oak, TN

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K504
Tuscan Manor Oak, TN

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY




Organic FLEX  waterproof


with **PerfectPad®** Cork 1 mm




K505



Flax River Oak
K502



K502
Flax River Oak, TN



K505
Tobacco Manor Oak, TN



Organic FLEX  waterproof

with PerfectPad® Cork 1 mm



638 mm
(25.12")
322 mm
(12.68")


Brooklyn Vibe
K509





K508
Brooklyn Mist, US

O.R.C.A.®
MOISTURE DEFENSE TECHNOLOGY



K509
Brooklyn Vibe, US

O.R.C.A.®
MOISTURE DEFENSE TECHNOLOGY



K510
Brooklyn Dark, US

O.R.C.A.®
MOISTURE DEFENSE TECHNOLOGY



rganic LONG

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



Thickness:
8 mm

Format:
2003 x 195 mm | 78.86" x 7.68"

Lock:
1clic 2go pure+



EN 13329



Silverdale Oak
K451




Organic LONG



2003 mm
(78.86")
195 mm
(7.68")

Silverdale Oak
K451





K451
Silverdale Oak, HO





K284
Summer Breeze Oak, RO




K450
Firebrand Oak, HO








K327
Hillside Oak, RO



K287
Steelworks Oak, HO



8156
Red River Hickory, VH



rganic CLASSIC


O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY




Thickness:
8 mm

Formats:
638 x 330 mm | 25.12" x 12.99"
1288 x 195 mm | 50.71" x 7.68"

Lock:
1clic 2go pure+



EN 13329



Tornado Oak
K395



rganic CLASSIC



1288 mm
(50.71")
195 mm
(7.68")

Misty Plains Oak
K231





K668
Mist Ethereal Oak, ET




K231
Misty Plains Oak, TO



K669
Rope Ethereal Oak, ET



Organic CLASSIC  waterproof



Solar Oak
K405

K406
Eurus Oak, NL

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K405
Solar Oak, NL

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



rganic CLASSIC



Golden Vista Oak
K230



K230
Golden Vista Oak, TO

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



5947
Historic Oak, HO

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY




K224
Wild West Oak, NL

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY






Tornado Oak
K395




K665
Copper Ethereal Oak, ET

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K395
Tornado Oak, NL

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K479
Espresso Carpenter Oak, CM

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY




Organic CLASSIC



Silverado Slate
K387





K385
Ice Flow, RT

O.R.C.A.®
MOISTURE DEFENSE TECHNOLOGY





K387
Silverado Slate, OS

O.R.C.A.®
MOISTURE DEFENSE TECHNOLOGY



Organic CLASSIC  waterproof



Crosstown Traffic
K035

K035
Crosstown Traffic, AS

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K389
Nightfall Slate, OS

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



Organic CLEVER SILENT

with PS Pad 1 mm

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



Thickness:
6+1 mm

Format:
1288 x 195 mm | 50.71" x 7.68"

Lock:
1clic 2go pure+



EN 13329



Rutherford Oak
K488



Organic CLEVER SILENT




with PS Pad 1 mm




1288 mm
(50.71")
195 mm
(7.68")

Colorado Oak
5543




5543
Colorado Oak, HC

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K063
Organic Oak, TO

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K452
Ashland Oak, HO

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



Organic CLEVER SILENT



with PS Pad 1 mm



Blackwater Oak
K413

K413
Blackwater Oak, OE

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



O.R.C.A. Flooring


K488
Rutherford Oak, CM

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY




rganic CLEVER SILENT 

with PS Pad 1 mm




Heathland Oak
K598




K598
Heathland Oak, HO

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K327
Hillside Oak, RO

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY



K489
Bourbon Hills Oak, HO

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY





Laminate Flooring Take more. Endure more. Withstand more.

mo.re! from KRONOSPAN is a moisture-resistant laminate flooring product that makes laminate even more practical for everyday life.



mo.re! makes laminate flooring even more moisture-resistant. And that's a good thing. After all, small everyday mishaps can happen to anyone.

How mo.re! technology works

mo.re! is based on a specially developed substrate formula.


Its new binding agent makes the flooring more durable and decreases swelling – improving resistance to moisture penetration.



Scan the QR code and check out the mo.re! features!

* 24 h surface water protection as stipulated by NALFA and 48 h splash-water protection according to works standard KRONOSPAN WN-103, www.floor-with-more.com





Your floor can do mo.re!

K476 Inca Carpenter Oak





mo.re! can stand up to what life brings



www.blauer-engel.de/uz176



It is **much more moisture-resistant** than traditional laminate flooring

It is **A.B.C. surface*** inhibits bacteria growth on floors to protect your family

It is **light-resistant**: Even on days when the sun is shining for hours, your flooring remains nonfading according to rating 6 of the Blue Wool Scale.


It is **perfect for life with house pets** – the robust and hard-wearing surface masters the everyday challenges of households with pets

It is great for **installation in private bathrooms****

It is available in **utilization classes 32 and 33** according to DIN EN 13329



* Tested germs: Staphylococcus aureus ** Please refer to the installation instructions



K326 Sundance Oak



mo.re! for the environment

mo.re! offers more, even for the environment

It is made using only wood from sustainably managed forests. And KRONOSPAN does not use any PVC in flooring with the mo.re! technology. This demonstrates our commitment to environmental stewardship. mo.re! substrate is CO₂-negative: Processing a tree to make this product emits less CO₂ than the tree has stored in its life.

* May contain traces of PVC, e.g. from packaging



HERRINGBONE 8



Thickness:
8 mm

Format:
630 x 126 mm | 24.80" x 4.96"

Lock:
Fold Down





EN 13329



Rutherford Oak
K488



HERRINGBONE 8



Sundance Oak
K326

K326
Sundance Oak, RO




5947
Historic Oak, HO




HERRINGBONE 8



Laguna Oak
K411



K488
Rutherford Oak, CM



K411
Laguna Oak, OE



ALTITUDE



Thickness:

12 mm

Format:

2003 x 245 mm | 78.86" x 9.65"

Lock:

1clic 2go pure+




EN 13329



Sundance Oak
K326




ALTITUDE




2003 mm
(78.86")
245 mm
(9.65")

Blonde Montreux Oak
K659






K659
Blonde Montreux Oak, MX



K658
Canvas Montreux Oak, MX



K657
Honey Montreux Oak, MX



ALTITUDE



Sundance Oak
K326

K326
Sundance Oak, RO



K662
Sepia Tegernsee Oak, TG



K664
Hare Tegernsee Oak, TG



ATLANTIC 12



Thickness:
12 mm

Format:
1288 x 195 mm | 50.71" x 7.68"

Lock:
1clic 2go pure+



EN 13329



Iceberg Oak
K336




ATLANTIC 12




1288 mm
(50.71")
195 mm
(7.68")

Iceberg Oak
K336






K336
Iceberg Oak, HC





5542
Boulder Oak, HC




K285
Haybridge Oak, HO




ATLANTIC 12



Inca Carpenter Oak
K476



K450
Firebrand Oak, HO



K476
Inca Carpenter Oak, CM



K287
Steelworks Oak, HO



ATLANTIC 10



Thickness:
10 mm

Format:
1288 x 195 mm | 50.71" x 7.68"

Lock:
1clic 2go pure+



EN 13329



Espresso Carpenter Oak
K479



ATLANTIC 10



1288 mm
(50.71")
195 mm
(7.68")

Virgin Scandi Larch
K475






K475
Virgin Scandi Larch, VS



K668
Mist Ethereal Oak, ET



K669
Rope Ethereal Oak, ET



ATLANTIC 10



Mushroom Carpenter Oak
K478

K667
Alpaca Ethereal Oak, ET



K478
Mushroom Carpenter Oak, CM



ATLANTIC 10



Inca Carpenter Oak
K476

K665
Copper Ethereal Oak, ET




K476
Inca Carpenter Oak, CM



5537
Tawny Chestnut, RC



ATLANTIC 10



Doublon Oak
K412


5947
Historic Oak, HO



K412
Doubloon Oak, OE




ATLANTIC 10



Laguna Oak
K411





K413
Blackwater Oak, OE




K411
Laguna Oak, OE




ATLANTIC 10




Appalachian Hickory
8155



8155
Appalachian Hickory, VH



8156
Red River Hickory, VH



K479
Espresso Carpenter Oak, CM



ATLANTIC 8



Thickness:
8 mm

Formats:
638 x 330 mm | 25.12" x 12.99"
1288 x 195 mm | 50.71" x 7.68"

Lock:
1 clic 2go pure+



EN 13329



Hillside Oak
K327




ATLANTIC 8




1288 mm
(50.71")
195 mm
(7.68")

Silverdale Oak
K451





K640
Cotton Greenvale Oak, MW



K451
Silverdale Oak, HO




K392
Atomic Oak, RO




ATLANTIC 8




Biscotti Oak
K453



K463
Weathered Volcano Oak, NL



K469
Tortilla Cashmere Oak, NL



K453
Biscotti Oak, HO



ATLANTIC 8



Sundance Oak
K326

K653
Ecrú Cantal Oak, MW



K326
Sundance Oak, RO




K327
Hillside Oak, RO




ATLANTIC 8




moisture
resistant




Antique Cashmere Oak
K471



K471
Antique Cashmere Oak, GT



K627
Caramel Pistachio Oak, MW





K649
Sienna Montreux Oak, MW




ATLANTIC 8



moisture
resistant




Antique Volcano Oak
K461




K634
Mushroom Apollo Oak, MW

mo.re!
moisture resistance technology



K461
Antique Volcano Oak, NL

mo.re!
moisture resistance technology



K650
Grizzly Montreux Oak, MW

mo.re!
moisture resistance technology



ATLANTIC 8



Crosstown Traffic
K035





K385

Ice Flow, RT

mo.re!
moisture resistance technology



4375

Pearl Grey Oxide, AS

mo.re!
moisture resistance technology



K035

Crosstown Traffic, AS



mo.re!
moisture resistance technology



ATLANTIC 8



Pewter Slate
K388



Classic

LAMINATE
FLOORING

Give your surroundings a unique flair



Laminate enjoys a fantastic reputation as an absolute all-rounder. There is hardly an area or room that is not suitable for its installation. Whether children's rooms or living rooms, offices or shops, with or without pets – laminate flooring is a beautiful and uncomplicated partner thanks to its robustness and durability.

The list of advantages of laminate flooring is long – easy to clean and therefore hygienic, anti bacterial thanks to surface structures that bacteria cannot adhere to, light-resistant and hard-wearing. Last but not least, there is the range of decors and surfaces, that leave nothing to be desired.

Authenticity you can see and feel

Very close to the original – these are laminate decors, whose appearance is made up of two factors – image and surface.

Color and light form the symbiosis for a perfect reproduction of wood, stone and tiles. And the perfect optical representation is complemented by the tactile reproduction. Vision and touch, the interaction of the senses.



5966 Khaki Oak



Fantastic look

K418 Longbow Oak

Classic

LAMINATE
FLOORING

Favourite for everyday living



www.blauer-engel.de/uz176



Easy to install


The sophisticated KronoOriginal® click systems make installation child's play. The prerequisite is good preparation – having all panel materials, accessories and tools at the ready, as well as planning with the help of the checklist and the appropriate instructions.

The floor for every requirement

An important factor when choosing a laminate floor is the utility class. The more a room is frequented and therefore the floor is challenged, the higher the usage class has to be. The utility class describes the possible stress on the entire panel and thus indicates whether the flooring is recommended mainly for private or also for commercial use. This consideration is important regarding to the warranty conditions.

Utilization class 32 (EN 13329)

Suitable for heavy domestic and medium commercial use





5966 Khaki Oak



Healthy living

A.B.C. – Anti Bacterial Comfort ensures that bacteria*¹, dust mites and microbes have no chance of settling on them. This makes cleaning the laminate flooring easier and quicker and therefore particularly hygienic.

Healthy living also means that additives such as PVC*², chloride or wood preservatives are not used and can therefore neither trigger nor intensify allergies.

Sustainable

Laminate flooring consists of around 90 percent natural wood, which comes exclusively from sustainably managed forestry. This is guaranteed by the PEFC certificate.

Generally, all production processes are low-emission and therefore sustainable.

^{*1} Tested germs: Staphylococcus aureus
^{*2} May contain traces of PVC, e.g. from packaging



SUPER NATURAL

Thickness:
8 mm

Format:
1288 x 195 mm | 50.71" x 7.68"

Lock:
1 clic 2go pure+



EN 13329



Credenza Oak
K338



SUPER NATURAL



↑ 1288 mm
(50.71")
195 mm
(7.68") →

Colorado Oak
5543

8630
Aspen Oak, LP




5543
Colorado Oak, HC



SUPER NATURAL




Boulder Oak
5542



K652
Cashew Montreux Oak, MW



K418
Longbow Oak, GT




5542
Boulder Oak, HC




SUPER NATURAL




Natural Sterling Oak
K485



K485
Natural Sterling Oak, NL



8575
Blonde Oak, LP



5966
Khaki Oak, NL



SUPER NATURAL



Rockford Oak
5946

5946
Rockford Oak, NL




K407
Ashenwood Oak, GT


SUPER NATURAL




Armoury Oak
K419



K641
Linen Sheridan Oak, MW



K419
Armoury Oak, GT



5985
Sherwood Oak, GT

SUPER NATURAL



Credenza Oak
K338

K638

Wheat Cornforth Oak, MW



K625

Wheat Pistachio Oak, MW



K338

Credenza Oak, NL



SUPER NATURAL



Clearwater Oak
K057


K057
Clearwater Oak, GT




8631
Castle Oak, LP




SUPER NATURAL






K629
Gold Fiordaliso Oak, MW



K633
Gold Apollo Oak, MW




8573
Harlech Oak, LP




SUPER NATURAL




Gondola Oak
K468



K468
Gondola Oak, GT



K647
Clay Sola Oak, MW



K635
Fawn Apollo Oak, MW



SUPER NATURAL



Twilight Sterling Oak
K482

K482
Twilight Sterling Oak, NL



K642
Flint Monticello Oak, MW



5541
Bedrock Oak, HC



CASTELLO

Thickness:
8 mm

Format:
1285 x 192 mm | 50.59" x 7.56"

Lock:
Twin clic



EN 13329



Natural Cashmere Oak
K470




CASTELLO




↑ 1285 mm
(50.59")

192 mm
(7.56") →


Gold Volcano Oak
K462



K470
Natural Cashmere Oak, GT



K656
Cabinwood Oak, MW



K462
Gold Volcano Oak, NL



CASTELLO



Tornado Oak
K395



K396
Skydive Oak, NL



K039
Silverside Driftwood, GT




K395
Tornado Oak, NL



Format overview



Plank Size	630 x 126 mm 24.80" x 4.96"	638 x 322 mm 25.12" x 12.68"	638 x 330 mm 25.12" x 12.99"	1210 x 192 mm 47.64" x 7.56"	1210 x 234 mm 47.64" x 9.21"	1210 x 295 mm 47.64" x 11.61"
Collection Name	Herringbone 8	Organic Flex Tile	Organic Classic Tile Atlantic 8 Tile	Rocko	Rocko	Rocko



Castello

Organic Flex

Organic Classic
 Organic Clever Silent
 Atlantic 12 | 10 | 8
 Super Natural

Organic Veneer Parquet

Organic Long

Altitude

Accessories that match your floor perfectly

Selected range of products

Every floor needs proper accessories. We can supply you with the ideal equipment for all types of flooring. One contact, one supplier – which makes everything so much simpler for you.

Underlays

Depending on the situation in the room, attention must be paid to the correct underlay material when installing the flooring. For this we offer multiple solutions.

Skirting boards

Choose from a range of skirtings in various decors that match all KronoOriginal® floors. Our advanced fixing system makes it quick and simple to achieve a perfect installation.

Additional accessories

If you still look for the proper skirting board, corner pieces, aluminium adhesive tape for sealing or you are done and wish to mop the floor, take a look at the following pages and discover the wide range of accessories.



All under one roof

Our guidance system shows the matching products for different types of floor.

Veneer Parquet

Organic VENEER PARQUET:
Height: 8.5 mm

SPC Flooring

SPC flooring:
Height: 5 mm and 5+1 mm, including silent pad, floating installation








O.R.C.A. Flooring

O.R.C.A. flooring:
Height: 6+1, 7 and 8 mm, organic rigid coreboard, floating installation








Laminate Flooring

Laminate flooring:
Height: 8, 10 and 12 mm








Underlays

Article	Illustration	Item No. [Customer Code]	Description	Packing Unit	Suitable for
Underlay PUR 1.0		98535 [EX PUR1.0_ORCA] 98535 [EX PUR1.0_SPC]	Material: PET film + polyurethane heavy- duty layer + non-woven material	1 x 10 m = 10 m ²	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Underlay PUR 2.0		98571 [EX KO98571N]	Material: Polyurethan and mineral fillers	1 x 7.5 m = 7.5 m ²	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Underlay WOOD 5.0		90171 [EX 90171.]	Material: Wood fibres	0.79 x 0.59 m x 15 = 7 m ²	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Underlay XPS 5.0		98536 [EX XPS5.0]	Material: Extruded polystyrene	1.18 x 4.7 m = 5.5 m ²	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Underlay XPS 2.2 ALU		98515 [EX XPS2.2ALU]	Material: HFPS-foam & moisture protection foil	1.2 x 12.5 m = 15 m ²	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
PE foil		98111 [EX FOLIE2.0]	Material: Polyethylene	2 x 7.5 m = 15 m ²	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Aluminium tape		98191 [EX ALUBAND]	Thickness: 0.048 mm Width: 50 mm	1 roll (50 m)	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring








Skirting boards

Article	Illustration	Item No. [Customer Code]	Description	Packing Unit	Suitable for
K58C		91061 [EX xxxxSLH]	2600 x 58 x 18 mm	10 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
K58C skirting board moisture resistant		97345 [EX SK58C-xxxx]	2400 x 58 x 18 mm	10 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
K58C skirting board for floors with O.R.C.A. (Moisture Defense Technology)		95316 [EX xxxxSLH-ORCA]	2600 x 58 x 18 mm	10 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Square cut skirting board		95951 [EX 9002DS19_100]	2600 x 100 x 17 mm	5 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Square cut skirting board		95481 [EX 9002DS19_70]	2600 x 70 x 17 mm	10 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Square cut skirting board		95491 [EX 9002DS19_58]	2600 x 58 x 17 mm	10 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Shaped skirting board		95981 [EX 9002DS17_100]	2600 x 100 x 17 mm	5 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring






Skirting boards

Article	Illustration	Item No. [Customer Code]	Description	Packing Unit	Suitable for
Shaped skirting board		95991 [EX 9002DS17_70]	2600 x 70 x 17 mm	10 pcs.	Veneer Parquet, SPC Flooring, O.R.C.A. Flooring, Laminate Flooring
Shaped skirting board		95471 [EX 9002DS17_58]	2600 x 58 x 17 mm	10 pcs.	Veneer Parquet, SPC Flooring, O.R.C.A. Flooring, Laminate Flooring
Rounded skirting board		96001 [EX 9002DS15_100]	2600 x 100 x 15 mm	5 pcs.	Veneer Parquet, SPC Flooring, O.R.C.A. Flooring, Laminate Flooring
Rounded skirting board		96021 [EX 9002DS16_90]	2600 x 90 x 16 mm	5 pcs.	Veneer Parquet, SPC Flooring, O.R.C.A. Flooring, Laminate Flooring
Rounded skirting board		96011 [EX 9002DS15_70]	2600 x 70 x 17 mm	10 pcs.	Veneer Parquet, SPC Flooring, O.R.C.A. Flooring, Laminate Flooring
Accessories for K58C skirting board		98011 98001 98021	External corners Internal corners End caps	90° in packs of 2 90° in packs of 2 in packs of 4, 2 left and 2 right	Veneer Parquet, SPC Flooring, O.R.C.A. Flooring, Laminate Flooring
Mounting clips		91501 [EX 50510]	-	Box of 30 pieces, complete with screws and rawl plugs	Veneer Parquet, SPC Flooring, O.R.C.A. Flooring, Laminate Flooring

Profile systems

Article	Illustration	Item No. [Customer Code]	Description	Packing Unit	Suitable for
Design click transition profile, 2-part		95112 95113	900 mm or 2700 mm	1 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Design click ramp profile, 2-part		95122 95123	900 mm or 2700 mm	1 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Design click end profile, 2-part		95132 95133	900 mm or 2700 mm	1 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Transition click profile		98391 98381	900 mm or 2700 mm	1 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
Ramp click profile		98411 98401	900 mm or 2700 mm	1 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
End click profile		98371 98361	900 mm or 2700 mm	1 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring
3in1 profiles		95315 [EX 95315-A002] anodised stainless steel	1000 mm	10 pcs.	Veneer Parquet SPC Flooring O.R.C.A. Flooring Laminate Flooring

Additional accessories

Article	Illustration	Item No. [Customer Code]	Description	Packing Unit	Suitable for
Tap-block		90274 [EX SCHLAGKLOTZ]	168/90 x 70 x 20 mm	20 pcs.	<div style="display: flex; gap: 5px;"> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Veneer Parquet</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">SPC Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">O.R.C.A. Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Laminate Flooring</div> </div>
Clickguard™ joint sealant		90431 [EX 94270]	-	125 ml ≈ ca. 10 m²	<div style="display: flex; gap: 5px;"> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Veneer Parquet</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">SPC Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">O.R.C.A. Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Laminate Flooring</div> </div>
Laminate cleaner		90411 [EX 92011]	-	1000 ml	<div style="display: flex; gap: 5px;"> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Veneer Parquet</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">SPC Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">O.R.C.A. Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Laminate Flooring</div> </div>
Design floor cleaner		97554 [EX DESIGNBODEN_ REINIGER]	-	750 ml	<div style="display: flex; gap: 5px;"> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Veneer Parquet</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">SPC Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">O.R.C.A. Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Laminate Flooring</div> </div>
Cleaner for floors with O.R.C.A. (Moisture Defense Technology)		90411 [EX REINIGER_ORCA]	-	750 ml	<div style="display: flex; gap: 5px;"> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Veneer Parquet</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">SPC Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">O.R.C.A. Flooring</div> <div style="border: 1px solid black; padding: 2px; font-size: 8px;">Laminate Flooring</div> </div>







































































































Skirting boards




Decor matching overview

	Collection Name	Decor	Skirting board	Decor	Skirting board	Decor	Skirting board
Veneer Parquet	Organic VENEER PARQUET	O272	9002-weiß	O274	9002-weiß	O352	9002-weiß
		O273	9002-weiß	O350	9002-weiß	O462	9002-weiß
SPC Flooring	ROCKO	R065	R065	R081	R081	R148	Z215
		R066	R066	R082	R082	R149	R124
		R070	R070	R109	R079	R150	Z212
		R073	R073	R123	R073	R170	R124
		R076	R076	R124	R124	R171	R091
		R077	R077	R125	R077	R172	R066
		R078	R078	R128	R073	R173	R073
		R079	R079	R129	R079	R174	R066
O.R.C.A. Flooring	Organic FLEX	K500	L133	K504	8836	K508	L137
		K501	4283	K505	8633	K509	L138
		K502	L134	K506	5542	K510	L139
	Organic LONG	K503	L135	K507	L129		
		8156	8156	K287	8096	K450	8816
	Organic CLASSIC	K284	8575	K327	8521	K451	L004
		5947	8285	K385	8282	K406	8575
		K035	4375	K387	L061	K479	L105
		K224	8634	K389	8475	K665	L118
		K230	8836	K395	L071	K668	8206
		K231	L003	K405	R002	K669	L121
		Organic CLEVER SILENT	5543	5543	K413	L064	K489
	K063		9855	K452	4275	K598	5549
K327	8521		K488	L128			
mo.rei Laminate Flooring	HERRINGBONE 8	5947	8285	K411	5539		
		K326	8836	K488	L128		
	ALTITUDE	K326	8836	K658	L120	K662	L125
		K657	8836	K659	8220	K664	L125
	ATLANTIC 12	5542	5542	K287	8096	K450	8816
		K285	4274	K336	L003	K476	8573

	Collection Name	Decor	Skirting board	Decor	Skirting board	Decor	Skirting board		
mo.rel Laminate Flooring	ATLANTIC 10	5537	8573	K412	8573	K479	L132		
		5947	8285	K413	L064	K665	L118		
		8155	8155	K475	5570	K667	9701		
		8156	8156	K476	8573	K668	8206		
		K411	5539	K478	5542	K669	L121		
	ATLANTIC 8	4375	4375	K389	8475	K471	L123		
		K035	4375	K392	L071	K627	8836		
		K326	8836	K451	8461	K634	8575		
		K327	8092	K453	9807	K640	9701		
		K385	8282	K461	L122	K649	5550		
		K387	L061	K463	8467	K650	Z149		
		K388	L062	K469	8220	K653	L143		
		Classic Laminate Flooring	SUPER NATURAL	5541	5541	8631	8631	K625	8837
				5542	5542	K057	8220	K629	8836
5543	5543			K338	4274	K633	R002		
5946	L004			K407	L070	K635	L123		
5966	5543			K418	L057	K638	8836		
5985	8573			K419	8220	K641	9855		
8573	8573			K468	5549	K642	5542		
8575	8575			K482	8374	K647	L123		
8630	8630			K485	4283	K652	9807		
CASTELLO	K039			L004	K396	L003	K470	8837	
	K395	L071	K462	5549	K656	8575			

Decor overview

Flooring Type	Collection Name	Decors
Veneer Parquet	Organic VENEER PARQUET	 O273  O462  O274  O350  O272  O352
SPC Flooring	ROCKO	 R079  R129  R078  R109  R148  R172  R174  R077  R065  R125
O.R.C.A. Flooring	Organic FLEX	 K500  K503  K506  K501  K507  K504  K502  K505  K508  K509
	Organic LONG	 K451  K284  K450  K327  K287  8156
	Organic CLASSIC	 K668  K231  K669  K406  K405  K230  5947  K224  K665  K395
	Organic CLEVER SILENT	 5543  K063  K452  K413  K488  K598  K327  K489
mo.re! Laminate Flooring	HERRINGBONE 8	 K326  5947  K488  K411
	ALTITUDE	 K659  K658  K657  K326  K662  K664
	ATLANTIC 12	 K336  5542  K285  K450  K476  K287
	ATLANTIC 10	 K475  K668  K669  K667  K478  K665  K476  5537  5947  K412
	ATLANTIC 8	 K640  K451  K392  K463  K469  K453  K653  K326  K327  K471
Classic Laminate Flooring	SUPER NATURAL	 8630  5543  K652  K418  5542  K485  8575  5966  5946  K407
	CASTELLO	 K470  K656  K462  K396  K039  K395



Packaging information

Flooring Type	Collection Name	Plank Size	Thickness	Planks/ Pack.	m ² sq ft/Pack.
Veneer Parquet	Organic VENEER PARQUET	1383 x 244 mm 54.45" x 9.61"	8.5 mm	7	2.36 25.42
SPC Flooring	ROCKO	1210 x 192 mm 47.64" x 7.56"	5+1 mm	7	1.63 17.54
		1210 x 192 mm 47.64" x 7.56"	5 mm	8	1.86 20.01
		1210 x 234 mm 47.64" x 9.21"	5 mm	7	1.98 21.30
		1210 x 295 mm 47.64" x 11.61"	5 mm	7	2.50 26.90
O.R.C.A. Flooring	Organic FLEX	638 x 322 mm 25.12" x 12.68"	7 mm	12	2.47 26.53
		1288 x 189 mm 50.71" x 7.44"	7 mm	10	2.43 26.19
	Organic LONG	2003 x 195 mm 78.86" x 7.68"	8 mm	7	2.73 29.42
	Organic CLASSIC	638 x 330 mm 25.12" x 12.99"	8 mm	11	2.32 24.92
		1288 x 195 mm 50.71" x 7.68"	8 mm	9	2.26 24.32
	Organic CLEVER SILENT	1288 x 195 mm 50.71" x 7.68"	6+1 mm	9	2.26 24.32
mo.re! Laminate Flooring	HERRINGBONE 8	630 x 126 mm 24.80" x 4.96"	8 mm	11	0.87 9.40
	ALTITUDE	2003 x 245 mm 78.86" x 9.65"	12 mm	4	1.96 21.12
	ATLANTIC 12	1288 x 195 mm 50.71" x 7.68"	12 mm	6	1.51 16.21
	ATLANTIC 10	1288 x 195 mm 50.71" x 7.68"	10 mm	7	1.76 18.92
	ATLANTIC 8	638 x 330 mm 25.12" x 12.99"	8 mm	11	2.32 24.92
		1288 x 195 mm 50.71" x 7.68"	8 mm	9	2.26 24.32
Classic Laminate Flooring	SUPER NATURAL	1288 x 195 mm 50.71" x 7.68"	8 mm	9	2.26 24.32
	CASTELLO	1285 x 192 mm 50.59" x 7.56"	8 mm	9	2.22 23.89


Weight/Pack. [kg lbs]	Pack./Pallet = m² sq ft
16 36	45 = 106 1144
16 35	60 = 98 1250
17 38	52 = 97 1040
19 41	48 = 95 1024
23 51	45 = 112 1210
16 35	32 = 79 849
16 35	52 = 127 1362
20 44	40 = 109 1177
17 38	32 = 74 797
17 36	52 = 118 1265
13 29	52 = 118 1265
6 13	96 = 84 902
20 44	36 = 71 760
15 34	52 = 78 843
15 33	52 = 91 984
15 34	32 = 74 797
15 34	52 = 118 1265
15 34	52 = 118 1265
15 34	52 = 115 1242



R129 White Poppy



Made by Kronospan



* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions). Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling – on a scale from A+ (very low-emission) to C (high-emission).

www.eco-institut.de/e/portfolio/emissions-dans-lair-interieur



www.krono-original.com
www.facebook.com/KronoOriginal



www.kronospan.com
info@krono-original.com